

# Logging and Profiling

In order to be able to log the **SLA Monitoring For Jira** app, you must activate logs as depicted in the screenshots below.

Administration

Search Jira admin

Back to project: Comité d'investissement

Applications

Projects

Issues

Manage apps

User management

Latest upgrade report

System

General configuration

Find more admin tools

SYSTEM SUPPORT

System info

Instrumentation

JMX Monitoring

Database monitoring

Integrity checker

Logging and profiling

Scheduler details

Troubleshooting and support tools

Audit Log

Settings

Advanced Settings

Edit Settings

General Settings

Title

Jira

Mode

Private

Maximum Authentication Attempts Allowed

3

CAPTCHA on signup

OFF

Base URL

http://localhost:8181

Email from

\$(fullname) (Jira)

Introduction

Internationalisation

## Default Loggers

Note that any changes you make here are *not persisted* across server restarts.  
You will need to edit 'WEB-INF/classes/log4j.properties' to change levels permanently.  
Logging will go to 'atlassian-jira.log'.

- **Configure** logging level for another package.

Default Loggers

Note that any changes  
You will need to edit 'W

Logging will go to 'atlas

• **Configure logg**

Package name

Default

atlassian-diagnostics

atlassian-diagnostics-data-loader

Configure logging level for another package.

Package name

com.keplertechnologies

Log4j logger name (e.g. 'com.atlassian.bonfire')

Logging Level

TRACE

Add

Cancel

INFO